

“79” Series Micro Swivel



Actual Size



This lightweight, compact and versatile swivel is constructed from heavy duty stainless steel and incorporated PTFE seals making it ideally suited to paint spray and chemical applications.

- Superior low friction swivel action
- Five piece construction, precision manufactured using 303 stainless steel
- Single PTFE washer
- One spring seal manufactured from Ultra High Molecular Weight Polyethylene (UHMWP)
- 8000psi maximum working pressure with a 4:1 safety factor
- Swivel function is guaranteed at all operating pressures from 1 – 8000psi
- Unique spring seal displays superiority over traditional methods
- Swiss made – Reliable, high quality engineering

PART. NO.	Thread Connection		Ø BORE	Maximum Working Pressure		Length	Weight
	INLET	OUTLET		BAR	Psi		
79-201/30	¼" NPS (M)	¼" NPSM (F)	3.5mm	550	8000	42mm	52g
79-202/30	¼" BSP (M)	¼" BSP (F)	3.5mm	550	8000	42mm	52g
79-212/30	¼" NPS (M)	¼" BSP (F)	3.5mm	550	8000	42mm	52g
79-221/30	¼" BSP (M)	¼" NPSM (F)	3.5mm	550	8000	42mm	52g

Exitflex (UK) Limited

3 Airfield Road, Airfield Industrial Estate, Christchurch, Dorset BH23 3TG

T: +44 (0)1202 478334 F: +44 (0)1202 488110 E: sales@exitflex.co.uk

www.exitflex.co.uk