

The advanced air-fed respiratory protection system for all spray operators.

The DeVilbiss Pro Visor air fed respiratory protection system has been purpose designed for use by sprayers.

The technically advanced design provides the perfect combination of safety and comfort in the spray booth, with excellent freedom of movement. The Pro Visor disperses breathing air gently around the lightweight visor at a positive pressure with no misting or discomfort, ensuring every sprayer can work at their best. The wrap around visor provides excellent and much wider peripheral vision, whilst the removable peak reduces glare from spray booth lighting. There is also plenty of space inside the helmet for sprayers who wear spectacles. Replaceable clear visor covers are available in packs of 10 or 50.

Typical Applications

- DeVilbiss Pro Visor is recommended for all spray operators.



Pro VISOR

Air Fed Respirator

- Purpose designed to provide best possible protection for all kinds of spray painting applications
- The most comfortable and lightweight air fed visor outfit
 - Fully adjustable head band for best operator comfort
 - Removable peak reduces spray booth light glare
 - Lightweight, Ergonomic waist belt design allows right or left side use
 - Wider peripheral view for excellent visibility
 - Audible warning device – alerts operator to low air pressure

Pro VISOR

Specification	
Protection	APF = 40 / NPF = 200
Carbon Filter Life	3 months
Supply Pressure	4.0 bar (60 psi) minimum to 7.0 bar (100 psi) maximum
Air Flow Rate	128 – 160 l/min (4.5 – 5.7 SCFM)
Noise level @ 160 l/min	69.7 db
Approvals	BSi & complies to CE PPE directive 89/686/EEC. Conforms to EN 14594:2005 Class 3A
Zone Classifications	Suitable for use in Zones 1 and 2 / gas groups IIA and IIB, Cert: SR0136

DeVilbiss Pro-Visor Part Numbers.

PROV-600	Complete visor, waist belt and hose outfit
PROV-20-K	Waist belt and regulator
PROV-21-K	Spare peak
PROV-22-K10	Peel off visors pack of 10
PROV-22-K50	Peel off visors pack of 50
PROV-23-K	Belt and buckle
PROV-25-K	Acetate visor face seal and air tube
PROV-26-K	Storage bag
PROV-27-K4	Filter element (Pk 4)
PROV-28-K4	Comfort brow band (Pk 4)
PROV-29-K	Visor head piece and breathing tube
PROV-30-K	Headband spacers and knobs (16 items - 1 set)
PROV-31-K	Threaded cap and seal for filter housing
PROV-32-K	Y-Piece assembly
PROV-33-K	QD connector with reducer



PROV-600



PROV-29-K



PROV-20-K

Warning Device

A whistle is incorporated to warn the operator that an insufficient quantity of breathing air is being supplied to the Pro-Visor. Should the whistle sound during use, the operator should vacate the spraying area immediately with the unit still on and check the air supply, i.e. look for crushed or cut supply hose.

Each time the Pro-Visor is used the device should be checked in a safe area, to do this the headpiece should be worn as normal and the air supply reduced to approximately 1 bar or less, this will cause the whistle to sound, when the pressure is restored to a safe level the whistle silences.

Best Protection


The unit is 'CE' marked to PPE Directive 89/686/EEC and conforms to EN 14594:2005 Class 3A. It is fully approved when used in accordance with these instructions.

This unit has a resistance to flammability in accordance with section 6.9 of EN 14594:2005. We recommend the unit to be used between the normal atmospheric temperatures of 0°C to 45°C. The visor is suitable for use in zones 1 and 2 hazardous areas with gas groups IIA and IIB, Certificate : SR0136.

The DeVilbiss air supply hose must be used at all times to maintain CE compliance.

Only use DeVilbiss genuine spare parts, to ensure CE approval and safety is maintained.

For more technical information please refer to the DeVilbiss Pro-Visor Service Bulletin.



Finishing Brands (UK) Limited
Ringwood Road, Bournemouth, Dorset
England BH11 9LH
Tel: +44 (0)1202 571111
Fax: +44 (0)1202 573488
Email: marketing-uk@finishingbrands.eu

Finishing Brands Germany GmbH
Justus-von-Liebig-Strasse 31,
63128 Dietzenbach Germany
Tel: +49 (0) 6074-403-233
Fax: +49 (0) 6074-403-281
Email: marketing-de@finishingbrands.eu

Surfaces et Finitions
163-171 Avenue des Auréats, BP 1453
26014 Valence cedex FRANCE
Tel: +33(0)4 75 75 27 00
Fax: +33(0)4 75 75 27 59
Email: marketing-fr@finishingbrands.eu